

Larsen Building Products Ltd

SLC Plus



Professional SLC 1550 Universal

By Larsen Building Products Ltd

Detailed description

Fast drying, hand or pump applied cement based underlayment. Manufactured from a controlled blend of special sands, cements and synthetic polymers to give a high quality flooring product which is self-levelling and smoothing. For use in fast track domestic and commercial situations such as where levelling of up to 50 mm is required. Suitable for use over underfloor heating and on more difficult substrates e.g. timber. It does not provide a wearing finish and must be overlaid with a suitable resilient floor finish, carpet, ceramic tiles, vinyl, resin coatings etc. Ideal for offices, dwellings, schools, hospitals and airports.

Product guidance - As Standard

Features:

- Form: Granular.
- Colour: Grey.
- Aggregate size (maximum): 1.2 mm.
- Bed thickness: 3–50 mm (minimum 10 mm when incorporating reinforcing mesh).
- Mix: 25 kg powder: 5 L water.
- Application temperature: + 5–30°C.
- Light traffic: 2–4 hours.
- Full traffic: 1–2 days.
- Coverage: 1 m² per 25 kg @ 12.5 mm.
- Screed compressive strength: 25 MPa.
- Single pack.
- Self levelling.

Product specification

Manufacturer

- Name: Larsen Building Products Ltd
- Web: www.larsenbuildingproducts.com
- Email: joris@larsenbuildingproducts.com

Product reference Professional SLC 1550 Universal

Primer Not required
Larsen acrylic primer diluted 1:1 with clean water - Normal concrete/ screed.
Larsen acrylic primer diluted 1:1 with clean water followed by a coat of neat acrylic primer - Particularly porous concrete/ screed.

